



Florida's Paint Manufacturer

Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 23rd Avenue • Fort Lauderdale, Florida 33311  
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833  
Toll Free: 800 273-1683 • Fax: 954 581-6085

## **24-100 ULTRA-PREP 100% ACRYLIC WOOD PRIMER**

**DESCRIPTION: HIGH PERFORMANCE 100% ACRYLIC WATER BASED PRIMER.** Formulated for priming bare wood. Excellent hiding, super adhering primer sealer that will seal most tannin stains when properly used and will also inhibit flash rusting.

**APPLICATION:** All surfaces must be cleaned to remove dirt, debris grease or oil which will interfere with the bonding of the primer. Primer may be applied by brush, roller, or spray. **DO NOT APPLY** when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY.** Stir and mix thoroughly prior to use. Dries in thirty minutes, re-coat in two hours.

**USES:**Excellent for use on interior or exterior surfaces. Uses include: wood, plaster, drywall, galvanized metal, concrete, stone, aluminum, interior steel, and as a wall covering sizing.

**THINNING & CLEAN UP** Thinning is not recommended, clean up with water.

Weight per gallon	11.55 lb.
Total solids by volume	38.00 %
Total solids by weight	44.00 %
Finish	Satin
Viscosity	100 Ku's

\*\* In areas of exceptionally strong stain bleeding, apply an additional coat of 24-100. For best performance allow 12 hours dry time between coats. Meets Federal Specification #TT-P-001984.