



24-111

U L T R A - P R E P

ACRYLIC STAIN BLOCKING SANDABLE INTERIOR WOOD PRIMER

EXTERIOR NON FERROUS METAL PRIMER

DESCRIPTION: **ULTRA-PREP IS A HIGH PERFORMANCE 100% ACRYLIC WATER BASED PRIMER/SEALER** that replaces oil based primers. **ULTRA-PREP** utilizing a new generation of water based technology. **ULTRA-PREP** is formulated for priming INTERIOR bare wood, or exterior non-ferrous metal substrates. **ULTRA-PREP** is sandable and services as an excellent foundation for subsequent coats of enamel coatings.. **ULTRA-PREP** will also seal stains on drywall or other types of interior substrates. **ULTRA-PREP** is a super adhering primer /sealer.

ULTRA-PREP is excellent for priming exterior sides of galvanized or factory primed metal doors or other non-ferrous metal substrates.

APPLICATION: All surfaces must be cleaned to remove dirt, debris grease or oil which will interfere with the bonding of the primer. Primer may be applied by brush, roller, or spray. **DO NOT APPLY** when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY**. Stir and mix thoroughly prior to use. **DO NOT THIN** Dries in thirty minutes, can be re-coated in two to four hours.

USES: Excellent for use on interior wood or exterior metal surfaces*. Uses include: wood, plaster, drywall, galvanized metal, concrete, stone, aluminum, and as a wall covering sizing, or an ultra high performance drywall primer that will block most stains.

THINNING & CLEAN UP Thinning is not recommended, clean up with water.

TECHNICAL

Weight per gallon	10.55 lb.	Total solids by volume	34.00 %
Viscosity	90 Ku's	Total solids by weight	47.00 %

***Not intended for use as a rust inhibitive primer** in areas of exceptionally strong stain bleeding, apply an additional coat of 24-111. For best performance allow 6 hours dry time between coats. Meets Federal Specification #TT-P-001984.