



*Paints Made
to Last in the
Florida Sun*

STUKO-SEAL
100%ACRYLIC LATEX
FRESH MASONRY SEALER
CODE #25-120

General Description

STUKO-SEAL is a Premium 100% acrylic pigmented new masonry sealer. STUKO-SEAL has a high resin content that provides excellent penetration and priming to sealing unpainted masonry for superior hold-out of subsequent coats of paint. The main function of this alkali resistant sealer is providing a barrier coat that will condition a porous substrate so that subsequent coatings will have proper long term adhesion.

Features

- Formulated to be a primer for new unpainted masonry.
- Excellent alkali barrier coating.
- Specifically to withstand our tropical climate
- Mildew and algae resistant
- Dries to the touch in about 15 minutes
- Durable and tough
- Excellent foundation for subsequent coats of paint on porous substrates.

Where to Use

- Excellent for all previously painted masonry or stucco surfaces (see surface preparation)
- Porous unpainted substrates such as:
 - Marcite®
 - Dryvit®
 - Pre-mixed colored stucco

Applications

- STUKO-SEAL may be brushed, rolled or sprayed.
- Use material directly from factory sealed containers.
- Do not apply when air or surface temperature is below 50 degrees (F).
- Must be primed to full opacity.
- Thinning is not required.

Benefits

- Promotes adhesion of the finish coat
- Binds residual POWDERY MASONRY
- Use over hot stucco Ph less than 12.
- Easy clean-up

Product Information

Product Information	
Colors: Pigmented	Technical Data (+ or – 3%)
Finish: Satin	Pigment by weights 28.0%
	Vehicle by weight 72.0%
	Weight per Gallon 11.22lbs.
Spread Rate: 250-450 sq. ft .per gallon depending on surface texture and porosity. Be sure to estimate right amount of paint for the job.	Total Solids by Weight 33.0%.
	Total Solids by Weight 46.0%
	Vehicle 100% Acrylic
	Viscosity 95;100- KU's
Dry Time: Dries in thirty minutes. Allow two hours dry time between coats	Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.

The information compiled herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the users responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

25-120 STUKO-SEAL
100% ACRYLIC LATEX
MASONRY PRIMER

Surface Preparation

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease and other foreign matter. Dull all glossy surfaces by sanding or de-glossing agent. For soffits and non exposed surfaces, wash or scrub with a detergent solution (TSP) and rinse well. Countersink nails and putty all holes.

NEW EXTERIOR MASONRY: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. Formulated for use on fresh unpainted stucco surfaces. Reduces the cure time needed in painting fresh masonry substrates. Provides an **ALKALI RESISTANT** barrier coat that will minimize efflorescence and protect the finish coat from alkali degradation.

All weather exposed MASONRY SURFACES should have a Ph less than 12. All stucco should be properly hydrated to insure proper results. Structural cracks and voids should be patched after sealing and prior to paint application.

WOOD: Sand smooth and apply primer as necessary. Consult UCI representative regarding primer recommendation. Holes and cracks should be puttied prior to painting.

FERROUS METAL: Prepared metal should be primed with UCI ULTRA-PRIME INDUSTRIAL METAL PRIMER 3-2000 or UCI AQUA-PRIME RUST PROOFER 3-2200.

NON-FERROUS METAL (Aluminum): Clean and prepare surfaces to ensure proper adhesion where bare prime with UCI ULTRA-PRIME INDUSTRIAL METAL PRIMER 3-2000

GALVANIZED METAL: All general surface preparations must be followed. On sound surfaces, no primer is required. If galvanized is oxidized, then priming with a latex primer is required such as UCI ULTRA-PREP 24-111.

CINDER BLOCK OR BLOWN STUCCO (POROUS SURFACES): All general surface preparations must be followed. Prime with UCI's block filler-sealer type paint, UNI-LASTIC MID-KOTE MASTIC 65-100.

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log onto www.epa.gov/lead

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN