



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 25th Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

DEKO-TEK

THE COST EFFECTIVE WATERPROOF, DECORATIVE DECK, AND SAFETY DECK COATING SYSTEM

DECORATIVE NON-SKID WATER RESISTANT

DESCRIPTION: DEKO-TEK is "state of the art" technology in a safety (non-skid) decorative, top quality 100% acrylic textured deck topping waterproofing system. DEKO-TEK dries to a satin textured finish that will re-finish almost any deck surface with a variety of multi-color designs. DEKO-TEK's durability and maintainability exceeds that of conventional waterproofing systems, floor paints and cementitious type topping systems. DEKO-TEK is mildew and water resistant, and can be used on a variety of flooring substrates such as concrete, wood, asphalt, and previously painted surfaces. Environmentally safe for interior or exterior applications, and cleans up with water and contain no harsh solvent odors.

Unlike most cementitious deck topping systems, DEKO-TEK is a 100% acrylic and can be applied to previously painted surfaces. *Deko-Tek decorative topping system offers unique properties such as:

FLEXIBILITY WATER RESISTANCE SAFETY (NON SLIP) TEXTURE TO HIDE SURFACE IMPERFECTIONS AND BLEMISHES AESTHETICALLY APPEALING FINISH

DEKO-TEK IS EASY TO MAINTAIN IN SUBSEQUENT YEARS DEKO-TEK CAN BE TOUCHED UP, REFINISHED OR RECOATED

RECOMMENDED USES: Formulated for use on all concrete, wood, or asphalt surfaces where a durable Waterproof safety coating finish is desired (see surface preparation). DEKO-TEK dries quickly with superior adhesion and affords a decorative textured finish. Ideal for catwalk deck, balconies, stairs, hallways and pool decks. Excellent for use on either interior or exterior applications.

APPLICATION: May be applied by brush, roller or "Hopper" spray. Do not apply when temperature is below 50 degrees. Stir and mix thoroughly before use. When rolling, a 1" synthetic nap is recommended on most surfaces. For best result when rolling, always splatter base coat color with a hopper to minimize roller lines. All previous coats of paint **MUST** have sound adhesion. For detailed preparation specifications consult manufacturer for written specifications.

DRYING TIME: Under normal conditions, DEKO-TEK will usually dry within 30-45 minutes, depending on temperature and humidity factors. For walking traffic, allow 2-4 hours. Clean tools with water immediately after use. **CAUTION:** Allow at least 10 days cure time for this coating to gain full strength and adhesion before washing the painted surface. High humidity or cold temperatures can significantly slow down the curing process.

CONSULT MANUFACTURER FOR SPECIFIC SPECIFICATIONS INCLUDING GENERAL SURFACE PREPARATION TECHNIQUES AND OTHER SPECIFIC INFORMATION