



*Paints Made to
Last in the
Florida Sun*

RAIN-KOTE PRIMER

**100% ACRYLIC ALKALI PROOF
CEMENTITIOUS WATERPROOFING
PIGMENTED ALIPHATIC SEALER
CODE #56-140**

General Description

The "RAIN-KOTE" can be used on above and below grade masonry. Rain-Kote waterproofs masonry, can also be used as a stucco or masonry curing compound. contains cement. The heavy application (10 dry mils) will penetrate (contains aliphatic solvent) in to cement substrate and will fill in hairline cracks application cracks (the coating contains cement). When fully cured at the proper mileage Rain-Kote will waterproof the cementitious substrate basically applying a 10-mil layer of waterproof cement. This process corrects the problem with the marginal cement substrates RAIN-KOTE should be top coated to protect the "Rain-Kote" from Uv exposure.

Features

- Alkali proof barrier sealer
- Waterproof unpainted masonry
- Provide an excellent foundation for subsequent coats of paint on porous masonry substrates.
- Seals minor chalky surfaces

Applications

- RAIN-KOTE may be brushed, rolled or sprayed*.
 - Use material directly from factory sealed containers.
 - Do not apply when surface temperature is below 50 degrees (F).
 - Application rate not to exceed 100 square feet per gallon
- *MUST REMOVE FILTERS IF SPRAYING, CONTAINS CEMENT

Where to Use

- Excellent for use on fresh concrete, masonry or stucco surfaces
- Porous unpainted substrates such as: Marcite®; DRI-VIT®; Pre-mixed colored stucco
- Waterproofing above and below grade concrete, masonry. stucco

Benefits

- Seals and waterproofs
- Promotes adhesion of the finish coat
- Binds residual chalk after pressure cleaning
- Mildew and algae resistant
- Hard coat waterproofing

Product Information

Product Information	
Colors: White pigmented	Technical Data (+ or – 3%)
Finish: Flat	100% Acrylic Solids 40.0%
	Cement and other pigments 60.0%
	Weight per Gallon 12.22 lb.
Spread Rate: 50-100 sq. ft. per gallon depending on surface texture and porosity.	Total Solis by Volume 40.0%.
	Total Solids by Weight 43.0%
	Vehicle 100% ALIPHATIC ACRYLIC
	Viscosity 85- 95 KU's
Dry Time: Dries in thirty minutes. Allow 6 hours dry time between coats	Thinning and Clean-Up: Thinning is not required. Clean with mineral spirits immediately after use.

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the user's responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

Surface Preparation

56-140 RAIN-KOTE MASONRY SEALER

FRESH MASONRY, STUCCO AND CONCRETE

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease and other foreign matter.

Stucco and masonry must be sound and dry enough to support coating application

PREVIOUSLY PAINTED EXTERIOR MASONRY: See factory representative before coating. All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All weather exposed surfaces must be pressure cleaned and mildew sanitized.

NOT FOR USE ON WOOD:

NOT FOR USE ON FERROUS AND NON-FERROUS METAL:

CINDER BLOCK OR BLOWN STUCCO (POROUS SURFACES):

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424. LEAD or log onto www.epa.gov/lead

WARNING! COMBUSTIBLE LIQUID AND VAPOR

Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation.

WARNING! Contains MINERAL SPIRITS.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and flame. Do not smoke.

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you have trouble in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN