



*Paints Made to
Last in the
Florida Sun*

BRITE WHITE ROOF PAINT ACRYLIC FLAT WHITE CODE # 8-111

General Description

An acrylic latex roof paint that dries to a tough, mildew resistant flat finish. Roofs painted with **BRITE WHITE** will stay whiter and cleaner longer than conventional roof paints. This coating contains a combination of fungicides including zinc oxide and algaecides to achieve maximum protection against topical contamination on a sanitized substrate. Mildewcides contained in paint will not aggressively kill existing mildew.

Features

- Formulated specifically to withstand tropical climate conditions
- White and custom colors are available

Where to Use

- Excellent for use on cement tiles (Flat or Barrel)
- Asphalt shingles
- Suitable for residential, commercial, or institutional applications.

Applications

- All surfaces must be cleaned to be free of grease, oil, dirt, or anything which will interfere with the adhesion of the product to be applied.
- Use material directly from factory sealed containers.
- All mildew: algae must be killed and sanitized before any paint applications
- This product may be applied by brush, roller, or airless spray
- DO NOT apply when temperature is below 50 degrees
- Always stir and mix thoroughly prior to use

Product Information	
Colors: White and Custom Colors	Technical Data
Finish: Flat	Pigment by Volume 13.00%
	Vehicle by Volume 20.00%
	Weight per gallon 10.50 lbs. +/-
Spread Rate: 200 sq. ft. per gallon depending on surface texture and porosity. Always apply to full opacity. Be sure to estimate right amount of paint for the job. Recommended film thickness: (approx.) Wet – 78 mils Dry – 2.5 mils	Total solids by weight 46.0%
	Total solids by volume 33.0%
	Vehicle: Acrylic latex
	Viscosity 100- 105 KU's
	Flashpoint: N/A
	VOC (less exempt solvents): ? 49 g/L; 041lb/gal
Dry Time: 30 minutes	Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.

The information compiled herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the user's responsibility to determine for their selves the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

**BRITE WHITE
ROOF PAINT
ACRYLIC FLAT WHITE
CODE # 8-111**

Surface Preparation

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease, and other foreign matter. Dull all glossy surfaces by sanding or de-glossing agent. For soffits and non-exposed surfaces, wash, or scrub with a detergent solution (TSP) and rinse well. Countersink nails and putty all holes.

NEW MASONRY SURFACES: All general surface preparations must be adhered to. To ensure proper coating life expectancy, all new masonry surfaces must be allowed to cure adequately. Do not paint over green or wet concrete: Wait at least 14 days prior to painting. Prime new masonry with UCI STUKO-PROOF 25-1000.

PREVIOUSLY PAINTED EXTERIOR MASONRY: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All weather exposed surfaces must be pressure cleaned and mildew sanitized with a chemical solution of "MILDEW PREP" and chlorine. All powdery, chalky weathered surfaces must be sealed with UCI UNI-SEAL ACRYLIC CLEAR SEALER 25-020 to ensure proper adhesion. Structural cracks and voids should be patched after sealing and prior to paint application.

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424.LEAD or log onto www.epa.gov/lead

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424.LEAD or log onto www.epa.gov/lead

Precautions **Contains** Zinc Oxide. May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin, and clothing. Do not take internally.

FIRST AID: If you have trouble in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100oF. Keep from freezing. Material Safety Data Sheet available upon request.

**CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN
CARCINOGENIC**

KEEP OUT OF REACH OF CHILDREN