



*Paints Made to
Last in the
Florida Sun*

FIBER-SEAL
100%ACRYLIC LATEX
CLEAR WATERPROOFING MASONRY
SEALER
CODE #65-000

General Description

FUGITIVE DYE

FIBER-SEAL is a unique FIBER REINFORCED clear 100% elastomer acrylic membrane masonry sealer. FIBER-SEAL has a high resin content that provides excellent penetration, chalk sealing and waterproofing of vertical masonry substrates. The main function of a sealer is to absorb and bind a deteriorated (chalky or oxidized) paint film, fill in minor cracks, and it will condition a porous substrate so that subsequent coatings will have proper long-term adhesion. FIBER-SEAL containing nylon fibers fill in minor cracks and waterproofs substrate to which it is properly

Features

- Formulated specifically to withstand our tropical climate
- Waterproofs vertical masonry substrates
- Seals chalky surfaces and provide an excellent foundation for subsequent coats of paint on porous substrates.
- Mildew and algae resistant
- Dries to the touch in about 15 minutes
- Durable and tough

CONTAINS A FUGITIVE DYE TO INSURE OPACITY.

Applications

- FIBER-SEAL may be brushed, rolled or sprayed*.
- Use material directly from factory sealed containers.
- Do not apply when air or surface temperature is below 50 degrees (F).
- Thinning is not required.

Where to Use

- Excellent for all previously painted chalky masonry or stucco surfaces
- Masonry surfaces that have water intrusion (See surface preparation)
- Porous unpainted substrates such as:
 - Marcite®
 - Dryvit®
 - Pre-mixed colored stucco

Benefits

- Promotes adhesion of the finish coat
- Binds residual chalk after pressure cleaning
- Waterproofs vertical masonry surfaces
- Fill in hairline cracks.
- Easy clean-up

Product Information

Colors: Clear		Technical Data (+ or – 3%)	
Finish: Satin and tacky		100% Acrylic Latex Solids	35.0%
		Water and Additives	50.0%
		Weight per Gallon	11.22 lbs.
Spread Rate: 150-300 sq. ft. per gallon depending on surface texture and porosity.		Total Solids by Volume	37.0%.
		Total Solids by Weight	39.0%
		Vehicle	Elastomer/Acrylic
		Viscosity	95-105 KU's
Dry Time: Dries in thirty minutes. Allow two hours dry time between coats		Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.	

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the user's responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

Surface Preparation

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease and other foreign matter. Dull all glossy surfaces by sanding or de-glossing agent. For soffits and non exposed surfaces, wash or scrub with a detergent solution (TSP) and rinse well. Countersink nails and putty all holes.

PREVIOUSLY PAINTED EXTERIOR MASONRY: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All weather exposed surfaces must be pressure cleaned and mildew sanitized with a chemical solution of 'MILDEW PREP' and chlorine. Visible Structural cracks and voids should be patched after sealing and prior to paint application.

NEW MASONRY STUCCO OR BLOWN STUCCO (POROUS SURFACES): Allow a minimum of one-week cure time for Ph of stucco to drop below 12. Spray and back roll.

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424. LEAD or log onto www.epa.gov/lead

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424. LEAD or log onto www.epa.gov/lead

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you have trouble in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN