



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 25th Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

STUKO-GUARD

ACRYLIC SATIN FINISH

EXTERIOR WALL PAINT

#42-100

DESCRIPTION: *STUKO-GUARD* is an acrylic exterior latex satin paint that is formulated for use in our tropical climate conditions on exterior substrates. *STUKO-GUARD* has good adhesion to properly prepared surfaces, with above average color fastness, and mildew resistance. Excellent for use on masonry, stucco, wood, composite siding, primed metal, and galvanized metal. Available in White, Off whites, and medium pastel tints.

USES: *STUKO-GUARD* is formulated as an exterior coating that will withstand our tropical climate conditions. Excellent for all masonry surfaces. (see surface preparation). Wood, masonite composites sidings, primed metal, Suitable for residential, commercial, or institutional applications. **(Consult manufacturer for warranty details and specifications).**

SURFACE PREPARATION: GENERAL: All surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk, oil, grease, and other foreign matter. Dull all glossy surfaces by sanding or deglossing agent. **(Consult manufacturer for specific detailed preparation specifications and procedures).**

DRY TIME: Dries in thirty minutes . Allow two hours dry time between coats.

THINNING & CLEAN-UP Thinning is not required, clean up with water.

TECHNICAL #42-100 WHITE BASE

Weight by gallon.....	10.80 lbs.
Total solids by volume.....	37.00%
Total Vehicle (Resin) solids by volume.....	22.3%
Viscosity.....	100-105KU's

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the users responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.
n:\udata\1-056-58-100