



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 23rd Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

FIBER-LASTIC ELASTOMER PATCHING

75-456

FIBER-LASTIC ELASTOMERIC FIBROUS PATCHING COMPOUND is a high technology product formulated with 100% acrylic elastomers and nylon type fibers. Fiber-lastic contains no additional plastizers. Fiber-Lastic is formulated for patching cracks ($\frac{1}{32}$ " to $\frac{1}{4}$ ") in masonry & stucco substrates. Seals and waterproofs between masonry, wood, glass, and brick.

TYPICAL USES: Waterproofing & Patching textured (non smooth) masonry & stucco substrates to include: cracks, joints, seams, roofs, parapets flashings. Excellent for use to waterproof seams between dissimilar substrates such as galvanized, aluminum, glass to masonry or concrete. Excellent for use to seal joints between above grade masonry, stucco, poured concrete & pre-cast.

CHARACTERISTICS: Very viscous, "fiber reinforce" textured trowelable high solids compound. A unique feature is that fibers are used in the manufacture of this product to give it outstanding lateral strength and integrity. The fiber reinforcement combined with the exceptional elasticity will insure a waterproof seal with superior crack bridging properties than a conventional textured patch.. May be applied in thick films without slump. Minimal-shrinking, permanently flexible. Paintable. Super adhesion. Mildew and Algae resistant.

CLEAN UP: Wash all equipment with warm detergent solution and rinse with water.

TECHNICAL DATA

FINISH: Low Sheen

VEHICLE TYPE: 100% Acrylic Elastomer

COATING SOLIDS BY: WEIGHT: 67%

VOLUME: 59% **VISCOSITY:** 160 & KU

FINISH: FIBER/TEXTURED

VOC: Less than 100 grams per liter

All cracks should be sounded out to determine if hollow or delamination of the stucco is present.

ALL PATCHING OF CRACKS WILL BE DONE AFTER SURFACES ARE PROPERLY PREPARED AND SEALED TO ENSURE THE ADHESION OF ANY PATCHING MATERIAL. WHEN FILLING JOINT OR CRACKS BE SURE TO "CROWN" THE PATCHING COMPOUND SO THAT A SMALL CREST REMAINS. THIS WILL COMPENSATE FOR ANY SLIGHT SHRINKAGE THAT MIGHT OCCUR.

DO NOT USE BELOW GRADE OR UNDER WATER. DO NOT APPLY when temperature of air and surface is **BELOW 40 degrees (F)**. Use caution if rain is imminent patch needs at least 4 hour of drytime. Allow new (fresh) concrete to cure for thirty days or prime with UCI # 56-140 "Rain-Kote", be sure to force Rain-Kote into crack.