



*Paints Made to
Last in the
Florida Sun*

STUKO-SEAL
100%ACRYLIC LATEX
FRESH MASONRY SEALER
CODE #25-120

General Description

STUKO-SEAL is a Premium 100% acrylic pigmented new masonry sealer. STUKO-SEAL has a high resin content that provides excellent penetration and priming to sealing unpainted masonry for superior hold-out of subsequent coats of paint. The main function of this alkali resistant sealer is providing a barrier coat that will condition a porous stucco substrate to resistant alkalinity, so that subsequent coatings will have proper long-term adhesion and durability.

Features

- Formulated to be a primer for new unpainted masonry.
- Excellent alkali barrier coating.
- Specifically, to withstand our tropical climate
- Mildew and algae resistant
- Dries to the touch in about 15 minutes
- Excellent foundation for subsequent coats of paint on porous substrates.

Where to Use

- Excellent for all unpainted fresh masonry or stucco surfaces.
- Formulated for use on High Ph masonry.
- Porous unpainted substrates such as:
 - Marcite®
 - Dryvit®
 - Pre-mix

Applications

- STUKO-SEAL roll, or spray& back roll, or cross spray with .a21 tip
- Use material directly from factory sealed containers.
- Do not apply when air or surface temperature is below 50 degrees (F).
- Must be primed to full opacity.
- Thinning is not required.

Benefits

- Promotes adhesion of the finish coat
- Binds residual POWDERY MASONRY
- Use over hot stucco Ph less than 12.
- Easy clean-up

Product Information

Colors: Pigmented	Technical Data (+ or – 3%)	
Finish: Satin	Pigment by weights	28.0%
	Vehicle by weight	72.0%
	Weight per Gallon	11.22lbs.
Spread Rate: 200-250 sq. ft .per gallon depending on surface texture and porosity. Be sure to estimate right amount of paint for the job.	Total Solids by Weight	38.0%.
	Total Solids by volume	50.0%
	Vehicle	100% Acrylic
	Viscosity	95;100- KU's
Dry Time: Dries in thirty minutes. Allow two hours dry time between coats	Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.	

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the user's responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

25-120 STUKO-SEAL
100% ACRYLIC LATEX
MASONRY PRIMER

Surface Preparation

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease, and other foreign matter. Dull all glossy surfaces by sanding or de-glossing agent. For soffits and non-exposed surfaces, wash, or scrub with a detergent solution (TSP) and rinse well. Countersink nails and putty all holes.

NEW EXTERIOR MASONRY: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt, and cracks. Formulated for use on fresh unpainted stucco surfaces. Reduces the cure time needed in painting fresh masonry substrates. Provides an **ALKALI RESISTANT** barrier coat that will minimize efflorescence and protect the finish coat from alkali degradation.

All weather exposed MASONRY SURFACES should have a Ph less than 12. All stucco should be properly hydrated to insure proper results. Structural cracks and voids should be patched after sealing and prior to paint application.

CINDER BLOCK OR BLOWN STUCCO (POROUS SURFACES): All general surface preparations must be followed. Intermediate coats such as UCI's block filler-sealer type paint or UNI-LASTIC MID-KOTE MASTIC 65-100 can be applied prior to finish coat.

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log onto www.epa.gov/lead

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log onto www.epa.gov/lead

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin, and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com