



Paints Made to Last in the Florida Sun **CODE# 80-100**

STUKO-FLEX
100 % ACRYLIC HIGH BUILD
EXTERIOR COATING
ALKALI RESISTANT*FLEXIBLE*
MILDEW RESISTANT

General Description

STUKO-FLEX is a high build, high performance exterior masonry coating that is specifically formulated for use in the Florida's climate over **NEW UNPAINTED STUCCO, CONCRETE OR CEMENT SUBSTRATES**. The unique feature of **STUKO-FLEX** is a water resistant, mildew resistant and alkali resistant flexible coating. The high solids of **STUKO-FLEX** enable the coating to fill and bridge naturally occurring application fissures in cementitious substrates. Minimizing efflorescence alkalinity burns. The performance and durability of **STUKO-FLEX** far exceeds that of a conventional paint on fresh masonry. **STUKO-FLEX** provides a water resistant barrier coating that dries to a satin finish that will both decorate and protect above grade exterior masonry surfaces.

Features and uses

STUKO-FLEX is formulated for use in the Florida climate where the fast pace of construction limits the time available to allow the stucco to hydrate and cure properly. **STUKO_FLEX** fills in and bridges minor application cracks

- Alkali resistant Mildew Resistant Flexible Finish Efflorescence Resistant
- Water-Resistant Excellent adhesion Chalk and fade resistant

Applications

STUKO-FLEX may be applied by brush, roller, or airless spray. Spraying and back rolling is preferred method of application **DO NOT EXCEED 125 square feet per gallon**. It is important to maintain wet and dry film thickness. **DO NOT THIN**, do not apply when temperature is below 50 degrees F. Dries to touch in ½ hour . Recoat under an

Product Information		
Colors: OFF WHITE; LIGHT TINTS	Technical Data (+ or – 3%)	
Finish: Satin	Total Solids by Volume	43.00%
	Resin Solid by Volume	25.00%
	Total Solids by Weight	55.00%
Spread Rate: Approx. 75- 125 sq. ft .per gallon depending on surface texture and porosity. Always apply to full opacity. Spray & back roll	Weight by Gallon	10.8 lbs.
	Vehicle	100% Acrylic
	Flashpoint	N/A
	VOC (less exempt solvents):	< 49g/l
Dry Time: Dries in thirty to forty minutes. Allow 1-hour dry time between coats	Viscosity	125-135 KU's
	Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.	

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENIC

Consult Technical representative for other options and detailed specifications.

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the users' responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary.

No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com

**STUKO-FLEX
HIGH BUILD ,HIGH SOLIDS
EXTERIOR SATIN
CODE # 80-100**

Surface Preparation

All surfaces must be clean, free of mildew, dirt, oil, grease, and other foreign matter that may cause an adhesion problem. Any loose or disbonded surfaces must be put into sound condition prior to painting. Spraying and backrolling yield the proper film build and texture to insure proper touch ups.

CONCRETE SURFACES: All general surface preparations must be adhered to. To ensure proper coating life expectancy, all new masonry surfaces must be sound and firmly adhered to underlying substrate. Hydrating stucco prior to painting is a good practice. Do not paint over green, powdery, or wet concrete: Pre-cast, tilt up solid panel concrete panels **MUST BE POWER WASHED THOROUGHLY** prior to coating applications

PREVIOUSLY PAINTED EXTERIOR MASONRY: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All weather exposed surfaces must be pressure cleaned and mildew sanitized with a chemical solution of 'MILDEW PREP" and chlorine. All powdery, chalky weathered surfaces must be sealed with UCI UNI-SEAL ACRYLIC CLEAR SEALER 25-020 to ensure proper adhesion. Structural cracks and voids should be patched after sealing and prior to paint application.
PREVIOUSLY PAINTED: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All chalky walls

CINDER BLOCK OR BLOWN STUCCO (POROUS SURFACES): All general surface preparations must be followed. Consult technical representative for detailed primer usage. Prime with UCI's block filler-sealer type paint, UNI-LASTIC MID-KOTE MASTIC 65-100.

Consult Technical representative for other options and detailed specifications.

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log onto www.epa.gov/lead

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com