



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 23rd Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

2-100 ULTRA-ALKYD SUPER GLOSS ENAMEL

DESCRIPTION: A durable alkyd (oil) based paint with a beautiful gloss enamel finish. Mildew and fade resistant, a scrubbable finish. Excellent flow and leveling. Interior or exterior use.

APPLICATION: All surfaces must be cleaned to be free of grease, oil, dirt, or any thing which will interfere with the adhesion of the product to be applied. Bare surfaces may require sanding to achieve a smooth finish. All bare surfaces must be primed completely. Brush, roller or spray application. **DO NOT apply** when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY.** Stir and mix thoroughly prior to use.

USES: Excellent for use on all surfaces where a hard, durable, washable water resistant gloss finish is required. Doors, Trim or Woodwork. Exterior metal.

THINNING &

CLEAN-UP: Thinning is **not recommended**, clean up with mineral spirits or wash thinner.

TECHNICAL:	Pigment by weight	28.00%
	T102.....	81.80%
	Zinc Oxide.....	4.00%
	Calcium Carbonate.....	14.20%
	Vehicle by weight	72.00%
	ALKYD Resin Solids.....	51.30%
	Thinner & Additives.....	48.70%
	Weight by gallon.....	9.70 lbs.
	Total solids by volume.....	52.00%
	Total solids by weight.....	40.00%
	Finish.....	gloss
	Viscosity.....	80-85KUs