



TIMBER-FLEX
100% ACRYLIC LATEX
HIGH BUILD WOOD COATING
CODE #67-100

Paints Made to Last in the Florida Sun

General Description

TIMBER-FLEX is a high build, high performance exterior wood coating that is specifically formulated for use in the Florida's

TIMBER-FLEX has been used on wood substrates in Florida since 1993. It was originally formulated for cedar shakes and T-1-11 siding. Florida's harsh humid rainy weather is very destructive on wooden exposures. **TIMBER-FLEX** is the ultimate exterior wood coating to protect and decorate wood siding or shingles.

Features and uses

HIGH FILM BUILD FINISH **PROTECTS WOOD FROM THE WEATHER**
FLEXIBILITY: **EXPANDS AND CONTRACTS WITH THE WOOD**
ADHESION: **ADHERES TO NUMEROUS SURFACES**
FILLS IN CRACKS, FISSURE AND VOIDS:

TIMBER-FLEX acts as a sealant preventing moisture from entering the wood via these openings. New wood often acquires hairline cracks, as evaporation of moisture within the wood occurs. Cracks are the first areas to show paint failure. **TIMBER-FLEX** will seal these areas.

Applications

TIMBER-FLEX may be applied by brush, roller, or airless spray. If application is by spraying back rolling is mandatory DO NOT EXCEED 125 square feet per gallon. It is important to maintain wet and dry film thickness. DO NOT THIN, do not apply when temperature is below 50 degrees F. Dries to touch in ½ hour.

Product Information		
Colors: ALL, (darker colors are suggested)	Technical Data (+ or – 3%)	
Finish: Satin	Total Solids by Volume	38.00%
	Resin Solid by Volume	30.00%
	Total Solids by Weight	50.00%
Spread Rate: Approx. 75- 1250 sq. ft .per gallon depending on surface texture and porosity. Always apply to full opacity. Spray & back roll	Weight by Gallon	10.8 lbs.
	Vehicle	100% Acrylic
	Flashpoint	N/A
	VOC (less exempt solvents):	< 49g/l
Dry Time: Dries in thirty to forty minutes. Allow 1-hour dry time between coats	Viscosity	125-135 KU's
	Thinning and Clean-Up: Thinning is not required. Clean with water immediately after use.	

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENIC

Consult Technical representative for other options and detailed specifications.

The information complied herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the users' responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary.

No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com

**STUKO-FLEX
HIGH BUILD ,HIGH SOLIDS
EXTERIOR SATIN
CODE # 80-100**

Surface Preparation

All surfaces must be clean, free of mildew, dirt, oil, grease, and other foreign matter that may cause an adhesion problem. Any loose or disbonded surfaces must be put into sound condition prior to painting. Spraying and backrolling yield the proper film build and texture to insure proper touch ups.

NEW WOOD SURFACES: All general surface preparations must be adhered to. To ensure proper coating life expectancy, all new surfaces must be THOROUGHLY CLEAN AND SANITIZED . No mildew, dirt, etc. Pressure treated wood must weather and needs to be detergent washed a power washed gentle, and allowed to dry completely

PREVIOUSLY PAINTED WOOD: All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling paint. All weather exposed surfaces must be pressure cleaned and mildew sanitized with a chemical solution of 'MILDEW PREP" and chlorine. All powdery, chalky weathered surfaces must be sealed with UCI UNI-SEAL ACRYLIC CLEAR SEALER 25-020 to ensure proper adhesion.

Consult Technical representative for other options and detailed specifications.

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin, and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log onto www.epa.gov/lead

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com