



1-100

UNI-ALKYD SEMI-GLOSS ENAMEL

DESCRIPTION: A durable alkyd (oil) based semi-gloss enamel. Excellent holdout, good flow and leveling. Perfect for spraying, Excellent one coat coverage over properly prepared surfaces. Interior or exterior use.

APPLICATION: All surfaces must be cleaned to be free of grease, oil, dirt, or any thing which will interfere with the adhesion of the product to be applied. Bare surfaces may require sanding to achieve a smooth finish. All bare surfaces must be primed completely. Brush, roller or spray application. **DO NOT apply** when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY.** Stir and mix thoroughly prior to use.

USES: Excellent for use on all surfaces where a durable washable semi gloss finish is required. Doors, Trim or Woodwork.

THINNING & CLEAN-UP: Thinning is not recommended, clean up with mineral spirits or wash thinner.

TECHNICAL:	Pigment by weight		42.02%
	T102.	47.90%	
	Zinc Oxide	4.20%	
	Calcium Carbonate	47.90%	
	Vehicle by weight		57.70%
	ALKYD Resin Solids	41.10%	
	Thinner & Additives	58.90%	
	Dry time:	2 hrs to touch; 18 hrs recoat	
	Spread rate	500 sq ft per gal	
	Weight by gallon		10.85 lbs.
	Total solids by volume	51.00%	
	Total solids by weight	64.00%	
	Voc	400 gms/L	
	Viscosity	90-95KU's	
	Finish	Semi-Gloss	