



*Paints Made to
Last in the
Florida Sun*

STONE GLAZE LOW ODOR SOLVENT ACRYLIC CLEAR SEALER CODE #25-1700

General Description

STONE-GLAZE is a Premium LOW ODOR SOLVENT acrylic clear sealer that has a high resin content that provides excellent substrate penetration. STONE GLAZE is mildew resistant "water clear" sealer that repels water and protects the underlying surface from UV degradation. Restores, protects and seals a variety of cement, brick, stone, pre-cast substrates. Stone glaze is also "drivable" when fully cured.

Features

- Formulated specifically to withstand our tropical climate
 - Mildew, algae, alkali resistant
 - Dries to a hard water clear finish
 - Durable and tough
 - Seals and protects most masonry, brick, block, and pavers
- Drivable when fully cured.

Warning may be slippery when wet. Use a non-slip agent on walkable pedestrian areas and surfaces.

Applications

- STONE-GLAZE may be brushed, rolled, or sprayed. Use material directly from factory sealed containers. Do not apply on wet or moisture containing surfaces when rain is imminent, or when air or surface temperature is below 50 degrees (F)

Thinning is not required.

Where to Use

- Stone, natural and casted, brick, pavers, concrete cementitious substrates
- Porous unpainted substrates such as:
 - Marcite®
 - Dryvit®
 - Pre-mixed colored stucco

EXTREMELY ALKALI RESISTANT CAN BE USED ON 'FRESH STUCCO'

Benefits

- Clear water-resistant finish
- Hard drivable finish
- Mildew algae and alkali resistant
- Fresh masonry or stucco to seal and waterproof

Product Information

Product Information	
Colors: Clear	Technical Data (+ or - 3%)
Finish: Gloss	Acrylic Solids 25.0%
	Diluents and Additives 75.0%
	Weight per Gallon 7.1lbs.
Spread Rate: 250-450 sq. ft. per gallon depending on surface texture and porosity. Be sure to estimate right amount of paint for the job.	Total Solids by Weight 25.0%
	Total Solids by Volume 19.0%
	Vehicle 100% Solvent Acrylic
	Viscosity 50-55 KU's
Dry Time: Dries in thirty minutes. Allow two hours dry time between coats	Thinning and Clean-Up: Thinning is not required. Clean with mineral spirits or VM&P Naphtha after use.

The information compiled herein is accurate to the best of our knowledge. We reserve the right to modify, adjust or improve any constituents contained herein. It is the user's responsibility to determine for himself the suitability of material for a specific purpose and to adopt such safety precautions as may be necessary. No representative of our company has the authority to change, modify or extend warranty without written consent from the corporate office.

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com

**STONE GLAZE
LOW ODOR SOLVENT
ACRYLIC
CLEAR SEALER
CODE #25-1700**

Surface Preparation

ALL surfaces must be clean, free of scaling, blistering, peeling paint, dirt, mildew, chalk oil, grease, and other foreign matter.

All general surface preparation must be followed. All surfaces must be clean and free from grease, oil, dirt and loose or scaling FOREIGN matter. All weather exposed surfaces must be pressure cleaned and mildew sanitized with a chemical solution of chlorine and rinsed.

ALL surfaces MUST COMPLETELY DRY AND MOISTURE FREE.

Consult Technical representative for other options and detailed specifications.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear an NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424.LEAD or log onto www.epa.gov/lead

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800. 424.LEAD or log onto www.epa.gov/lead

Precautions May cause eye, skin, and nose and throat irritation.

USE ONLY WITH ADEQUATE VENTILATION: To avoid breathing vapor, spray mist, or sanding dust, open windows and doors or use other means to ensure fresh air entry during sanding, application, and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (MOSHMSHA TC 23C or equivalent) or leave area. Close container after each use. Avoid contact with eyes, skin, and clothing. Do not take internally.

FIRST AID: If you experience difficulty in breathing, leave area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

Keep container closed when not in use. Do not store above 100°F. Keep from freezing. Material Safety Data Sheet available upon request.

CONTAINS NO CRYSTALLINE SILICA OR ETHYLENE GLYCOL KNOWN CARCINOGENICS

KEEP OUT OF REACH OF CHILDREN

UCI PAINTS · 1320 N.W. 23RD AVENUE · FORT LAUDERDALE, FL 33311 · 800.273.1683 www.ucipaints.com