



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 23rd Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

3-150

ACRYLIC BLOCK FILLER

DESCRIPTION: A 100% acrylic "high solids" water-based coating that is formulated to be a prime coat on porous masonry substrates, including CBS block. The high solids and alkali resistant 100% acrylic binder enables this product, when applied properly, to be an excellent foundation by filling in minor voids and sealing masonry cement-type surfaces.

APPLICATION: May be applied by brush, roller or spray. Spray & backroll is the preferred method of application. Spread rate not to exceed 100 square feet per gallon to achieve desired results. Certain irregular surfaces may require two coats for best performance. **DO NOT apply** when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY.** Stir and mix thoroughly prior to use. Dries in thirty minutes. Recoat in two hours.

USES: Formulated to seal and fill in CBS block and other porous type substrates such as blown stucco and unpainted conventional stucco. The High solids and high build nature of this coating provide an excellent foundation for subsequent finish coats of paint. The 100% acrylic resin makes this coating extremely alkali resistant and can be applied to almost any type of cement substrate.

**THINNING &
CLEAN-UP:**

Thinning is not required. Clean up with water.

TECHNICAL:

Weight per gallon.....	12.95.
Total solids by volume.....	47.00%
Total solids by weight.....	59.00%
Finish.....	Matte
Viscosity.....	125-128KUs