

85-100

DURA FLAT

100% ACRYLIC ROOF PAINT

DESCRIPTION: A 100% acrylic latex roof coating that dries to a tough, mildew resistant "DEAD FLAT" finish. Roofs painted with **DURA FLAT** will minimize any existing surface imperfections better than conventional roof paints. This coating contains a combination of fungicides including zinc oxide to achieve maximum mildew protection.

APPLICATION: All surfaces must be cleaned to be free of grease, oil, dirt, or any thing which will interfere with the adhesion of the product to be applied. All mildew must be killed and removed before any applications. May be applied by brush, roller or spray. **DO NOT** apply when temperature is below 50 degrees. Stir and mix thoroughly prior to use.

USES: Formulated to stand tropical climate conditions. Excellent for use on cement tiles flat or barrel , mansard roofs, and asphalt shingles. This product should be used where a mansard roof (45 degree angle) is to be repainted . The "dead flat " finish will help to minimize surface irregularities. Custom colors are available.

THINNING & CLEAN-UP: Thinning is not recommended. Clean up with water Dries in 30 minutes to touch 2 hours to recoat.

TECHNICAL:	Pigment by weight.....	35.00%
	Tio2	40%* depending on color
	Zinc oxide	10%
	Feldspar	50%
	Vehicle by weight.....	65.00%
	Acrylic emulsion	35% (50% solids)
	Opaque polymer	9%
	Additives & Mildewcides	6%
	Water	50%
	Weight by gallon.....	11.50 lbs.
	Total solids by volume.....	34.00%
	Total solids by weight.....	48.00%
	Finish.....	Flat
	Viscosity.....	100-105KU's