



Florida's Paint Manufacturer
Architectural Coatings • Deck Coatings • Roof Coatings • Sundries • Waterproofing Systems

1320 NW 25th Avenue • Fort Lauderdale, Florida 33311
Broward: 954 581-6060 • Dade: 305 945-4300 • Boca: 561 428-5833
Toll Free: 800 273-1683 • Fax: 954 581-6085

UNI-LATEX ENAMEL DRYFALL ENAMEL PRODUCT CODE 5-100DF

- DESCRIPTION:** A 100% acrylic "DRYFALL" enamel. Specially formulated for airless spray so that the paint will dry before the overspray hits the ground (8 foot drop). Available in White, black, or custom colors.
- APPLICATION:** May be applied by brush or roller, or spray. But airless spray yields the best results and finish. **DO NOT** apply when temperature is below 50 degrees. **FILTERED FOR AIRLESS SPRAY.** Stir and mix thoroughly prior to use.
- USES:** Excellent for use on all overhead surfaces that require fast-dry, to minimize overspray adhering to adjacent surfaces. The film dries to a durable washable finish. Excellent for all masonry or primed metal surfaces. This coating can also be used on conventional surfaces such as: Doors, Trim or Woodwork. As with any coating proper surface preparation procedures must be strictly followed. This product may be used interior or exterior.
- THINNING & CLEAN-UP:** Thinning is not required. Clean up with water.
- TECHNICAL:**
- | | |
|-----------------------------|--------------------|
| Pigment by weight..... | 30.00% |
| Vehicle by weight..... | 70.00% |
| Weight by gallon..... | 10.50 lbs. |
| Total solids by volume..... | 36.00% |
| Total solids by weight..... | 50.00% |
| Finish..... | Enamel |
| Viscosity..... | 90-95KU's |
| Coverage..... | 250-400 sq. ft/gal |